


Beam Clamps

Beam Clamps — Malleable Iron, Silver Electroplated Finish



CAT. NO.	BASE SIZE (IN.)		JAW OPENING (IN.)	TAPPING OF BASE AND BACK HOLES	SET SCREW LOAD RATING†	TORQUE IN INCH-LBS.	STD. CTN.
	A	B					
500-SC	1	1¼	1⅞	¼-20	250	60	50
501	1½	1⅞	⅞	¼-18	500	60	50
502	2	2	1	⅜-16	750	120	50
503-SC	2⅝	2½	1	½-13	1,250	250	20
507	2½	2⅝	1⅞	½-13	1,250	250	20
508	2½	2⅝	2⅞	½-13	1,250	250	10
509	1	1¼	1⅞	10-24	150	60	100
510	2⅞	1⅞	⅞	¼-20	250	40	100
511-SC	2⅞	1⅞	⅞	10-24	150	40	100


†Safety Factor of 3.

Load Ratings based on bottom hole of Beam Clamp.

CSA File No. LR-52208.

Also available in 316 stainless steel.


U-540 — Side Hanger Clip



CAT. NO.	A (IN.)	B (IN.)	C (IN.)	D (IN.)	STD. CTN.
540 3/8	7/16	1⅞	¼	7/8	25
540 1/2 EC	9/16	1⅞	¼	1⅞	25
540-5/8	11/16	2½	¾	2	25
540-3/4	13/16	2½	¾	2	25


Finishes — GoldGalv® brand or Black (B)

U-542 — Side Hanger Clip




CAT. NO.	ROD SIZE	DESIGN LOAD (LBS.)
544	¾"	610
	½"	1,000


Finishes — GoldGalv® brand or Black (B)
Standard Finish — GoldGalv®, EG, HD, & SS available.




U562
Beam Clamp
½" set screw included.
Rod Size: ½"
Design load 500 lbs.




U562
Beam Clamp Optional Use
½" set screw included.
Rod size: ½"
Design load 800 lbs.
For 20° swivel application,
use ES-145-1/2 nut.




U563
Beam Clamp Optional Use
¾" set screw included.
Rod size: ¾"
Design load 400 lbs.




U563
Beam Clamp with Swing Hanger
¾" set screw included.
Rod sizes: ¾"
Design load 540 lbs.




U562
Beam Clamp with Swing Hanger
½" screw included.
Rod size: ½"
Design load 800 lbs.



U563
Beam Clamp
¾" set screw included.
Rod size: ¾"
Design load 250 lbs.



U-568
Beam Clamp Safety Strap
Standard Finish — GoldGalv® brand
For U-563 beam clamp.



U-568
Beam Clamp Safety Strap
Standard Finish — GoldGalv® brand
For U-562 beam clamp.