



Pass and Seymour  
15A Single Pole, Double Throw Switch, White  
Part No. 1250W



Single-Pole, Double-Throw Switch. 15A, 120/277VAC rating. Tested to 3 Amps, 24Vdc rating.

## Features & Benefits

Oversize silver alloy contacts for long life and better heat dissipation.

Side wired terminals accept #14 - #10 AWG copper or copper-clad conductors.

Fiber terminal insulation barriers standard.

Can be mounted in standard device boxes or in NEMA 1 sheet steel enclosures.

Bodies, covers, and toggles molded of durable nylon.

Single Pole-Double Throw and Double Pole-Double Throw.

Locking Switches supplied with one 1498-NT key.

Normally open.

For covering patents, see [www.legrand.us/patents](http://www.legrand.us/patents).

For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, [click here](#).

## Specifications

### General Info

Product Line	Pass & Seymour	Color	White
Finish	Matte	UPC Number	785007125146
Country Of Origin	Mexico	Material	Nylon
Switch Type	Momentary	Application Sector	Commercial, Residential
Standard	UL listed	Type	Switch

### Dimensions

---

Product Width US	1.5 in	Product Depth US	1.469 in
------------------	--------	------------------	----------

---

Product Height US	3.281 in
-------------------	----------

---

### Listing Agencies / 3rd Party Agencies

---

CSA Listed	Yes	cULus ListingNumber	31169
------------	-----	---------------------	-------

---

cULus Listed	Yes	CSA File Number	17949
--------------	-----	-----------------	-------

---

### Technical Information

---

Throw Type	Double Throw	Amperage	15 A
------------	--------------	----------	------

---

Number of Poles	Single Pole	Wire Size	#14 - #10 AWG
-----------------	-------------	-----------	---------------

---

Mounting Type	Box	Voltage	120/277 V
---------------	-----	---------	-----------

---